

TECHNICAL DATA SHEET

High performance pvc sheet for civil and industrial flooring. (Art. 401)

Classification

Typology	EN 10581	PVC flooring
Commercial classification	EN ISO 10874	34 Heavy
Light industrial classification	EN ISO 10874	41 Moderate

Technical features

Total thickness	EN 24346	3,3 mm
Wear layer		> 1,5 mm
Weight	EN 23997	4,2 kg/sqm
Surface		Large coin Ø 20 mm

Performance

Fire reaction	EN 13501-1	Bfl-s1	
Volume resistivity	EN 21920	3,8 x 10 ¹⁵ ohm-cm	
Residual indentation	EN 24343	0,09 mm	
Coefficient of friction	EN 13893	DS Class	
Light resistance	ISO 105-B02	> 7	
Resistance to solvents	UNI 5574	As is	1,3 mm
		Petrol	1,0 mm
		Mineral oil SAE 20W	0,7 mm
		Detergent Antarox CO-360	1,5 mm
		Hydrochloric acid 10%	1,5 mm
		2% NaOH aqueous solution	1,0 mm

Environment

REACH regulation	Does not contain SVHC substances
Recyclability	100% recyclable

Format and dimensions

Sheet	EN 24341	98 cm x 20 m
-------	----------	--------------

