

COLLECTION

WOOD & CONCRETE

HIGH RESISTANCE
CLICK PVC FLOOR






GENiUS

SOGEGA

THE NATURE OF PLASTICS

WOOD & CONCRETE



Our coupling system makes installation quick and simple (dis. 1,2,3)

Material:

Heterogeneous PVC

Format:

Planks/Tiles click system

Dimensions:

Planks 1524x228 mm

Tiles 935x465 mm

Thickness:

5.5 mm total (Wood)

6.0 mm total (Concrete)

Wear layer 0.55 mm

1,5 mm IXPE mat (Wood)

1 mm IXPE mat (Concrete)

Weight:

8.40 kg/m² (Wood)

10.50 kg/m² (Concrete)

Finish:

Wood-effect planks with 3D embossing in register

Concrete-effect tiles

QUANTITY PER PACK:

7 Planks 2,44 m²

5 Tiles 2,17 m²



Reaction to fire:

Bfl-s1

Slip resistance: R10

Friction coefficient:

Class DS

Static electrical propensity:

EN 1815 < 2kV (Antistatic)

Dimensional stability:

EN 23999 ≤ 0.15%

Acoustic insulation:

ΔLw 20DB

Castor chair: Pass

Residual indentation < 0.1 mm

Light resistance:

Grade 6

Fungi resistance:

Growth 0

Air quality in relation to the environment:

TVOC emissions

French Reg. A+

Emissions Formaldehyde

Class E1 (does not contain

Formaldehyde)

REACH regulation:

It does not contain substances mentioned in the SVHC list

UV coating
Wear layer 0,55 mm
Film deco HD
Rigid solid core
Acoustic insulation layer IXPE 20 db



Sistema Qualità ISO 9001 cert. n° 782