

THE ELEGANCE OF DESIGN, THE CHARM OF TRADITION

INTRECCIO

WOVEN VINYL
FLOORING



INTRECCIO

Produced by intertwining vinyl material threads, it is a highly resistant floor that combines modern design and ease of installation. Particularly suitable for highly frequented places, such as offices or shops, which require of a floor that is easy to maintain and with an attractive appearance.

INTRECCIO Art. 1160

Material:
vinyl fabric

Format:
rolls

Length:
2 m

Length:
20m

Thickness:
2,5 mm

Weight:
2,7 kg/mq

Finish:
Decorative fabric

Reaction to fire:
Bfl-s1

Friction coefficient:
Class DS

Anti-static properties:
≤ 2kV (Antistatic)

Dimensional stability:
< 0.25%

Curvature:
< 2 mm

Heat resistance:
Suitable for underfloor heating

Soundproofing:
ΔLw 11 dB

Wheelchairs:
Continuous use

Light resistance:
> 6

Air quality in relation to the environment:
Smoke density < 450

Formaldehyde emissions:
N. 1911060065HF-004



Carry out installation at an ambient temperature of at least 18°C, maintaining this condition for 24 hours before and after installation.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de nuisance par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Sistema Qualità ISO 9001 cert. n° 782