

INVISIBLE STRENGTH, EVIDENT RESISTANCE

ACRIWHEEL

HIGH EFFICIENCY
SELF-LOCKING FLOOR

SMART




SOGESA

THE NATURE OF PLASTICS

ACRIWHEEL SMART



Travertine



Basalt



Thickness

6.0 mm

Weight

11 kg/mq ca.

Format

930x580 mm

self-laying puzzle-cut

interlocking plates

Packaging

Loose on pallet

ACRIWHEEL SMART

is the latest addition to the series. Its composition of plastic polymer and mineral material, combined with the presence of a glass fiber mesh, gives it excellent dimensional stability.

Furthermore, the total thickness of 6 mm, with a wear layer of 0.70 mm, makes it suitable for the passage of particular loads, such as forklifts or pallet trucks with rubber wheels.



PUZZLE CUT

Reaction to fire:

CE class Bfl-s1

Slip resistance:

Class R10

Friction coefficient:

Class DS

Dimensional stability:

≤ 0.15%

Residual indentation:

ISO 24343 ≤ 0.1 mm

Light fastness:

6-7 scala dei blu

Abrasion resistance:

Gruppo T

Resistance to chemicals:

Test passed

Resistance to microorganisms:

Growth 0

Carry out the installation at an ambient temperature of at least 18°C, maintaining this condition for the 24 hours before and after installation.

Always check the conditions of the installation rooms with our technical office.



RICICLABILE
BASSO IMPATTO
AMBIENTALE



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de nocivité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Sistema Qualità ISO 9001 cert. n° 782